

Product code: 4-IL2B-01358

RI-6991/50 PET CLEAR TC AP906-40 PET100 AUTOMOTIVE GRADE

A wide offer of products for decorative purpose such as for black-out applications on pillars, strips for body-car parts decorations, decorative labels and doming for luxury decorations and identification markings.

Applications

Promotional and decorative labels, specifically developed for doming.

Face Material

Gloss clear top coated polyester.

Type	Top coated polyester	
Colour and Finish	Gloss clear	
Weight	70 g/m ² ±10%	ISO-536
Thickness	50 µm ±10%	ISO 534-80

Adhesive

Acrylic permanent adhesive featuring high clarity and very high cohesion. Designed for a wide variety of substrates such as glass, ABS, PS, PVC. Unsuitable for apolar surfaces (like PE and PP).

Reference	AP906	
Type	Acrylic permanent	
Min. Appl. Temp.	+10 °C	
Service Temperature	-20°C/+140°C	
Shear	Very High	FINAT FTM8
Initial adhesion	> 8 N/25mm	FINAT FTM1
Final Adhesion	> 13 N/25mm	FINAT FTM1

Liner

Type	One side siliconised polyester	
Colour and Finish	Clear	
Weight	140 g/m ² ±10%	ISO-536
Thickness	100 µm ±10%	ISO 534-80
Transparency	> 90 %	DIN 53 147-64

Printing Methods

Suitable for UV and solvent based screenprinting and UV offset printing.

Shelf life

24 months, applicable only to the material delivered by Ritrama which has not undergone further processing, under the storage conditions as defined by FINAT section 2.5:

- Ideal storage conditions are at a temperature of 20 -25 °C and 40 - 50 % HR.
- Store in a cool and dry place.
- Do not store close to a heat source or in direct sunlight.
- Keep the material in the original packaging until required for use.

Pay particular attention to the recommended shelf-life and ensure correct stock rotation.

Disclaimer

All Ritrama's products are subject to manufacturing controls in order to guarantee the good quality of the products. The statements, technical information, data, values and recommendations regarding Ritrama's products are based on research and tests we believe to be reliable, but do not constitute a guarantee or warranty of whatsoever nature.

Considering the multiple uses of Ritrama's products, the user is recommended to test the products prior to their use, so to determine and ascertain the suitability and performance of the product for its intended application and purpose.

The methods of conversion and application of Ritrama's self-adhesive materials are multiple and it is therefore essential that the users are aware of the particular method to be used, prior to commencing the production.

Printing: testing for compatibility between product, printers and inks is always highly recommended before printing the product.

Application Systems and Conditions: it is recommended that the performance of the product be always tested in the actual applications conditions as to humidity and moisture; temperature; substrate state (rough, smooth, flat or irregular shapes, small containers or very large); direct contact with the substance into the container; applicator technology (hand application, multi headed fully automated at high speed); specific stress on Ritrama material once applied (high and/or low temperature, mechanical stress, rubbing, exposure to challenging environment conditions), et cetera.

As Ritrama's products are used in conditions beyond its control, such as those listed above as example, Ritrama does not assume any liability for inappropriate use of the products.

Ritrama reserves the right to modify at any time and without the need of a prior notice, at its sole and exclusive discretion, the products, their features and technical specifications.

All Ritrama's products are sold subject to Ritrama's general terms and conditions of sale listed in the following Ritrama's web page: www.ritrama.com/en/sale-conditions/