

## Magnetic Sheeting – Plain Brown

### PRODUCT DESCRIPTION:

- Consist of high coercive ferrite powders and high quality thermoplastics.
- Isotropic and Anisotropic magnetic materials are available
- Magnetic Sheeting has a UV hardened coating on the magnetic side.
- Easy to cut, apply, remove and change.

### USE AND STORAGE:


- Working Temperature: 10°C - 35°C, Short Term Resistance: 50°C, Relative Humidity: 20% - 60%.
- Handling: Keep away from open flame or other non-processing sources of ignition.
- Storage: Avoid sunlight, temperature 10°C - 35°C, relative humidity 20% - 60%.
- Shelf life: 12 months, unfinished product should be re-packed and kept in normal storage conditions.

### DIMENSIONS:


WIDTH: 620mm, 1000mm, 1200mm

LENGTH: 15M, 20M, 30M

### PACKAGING:



3" core



↑ Tray & Lid box

### PHYSICAL PROPERTIES:

Flexibility: Can be wrapped around a rod with a 12mm radius at 20°C without cracking.

Cutting: Scissor cutting, knife-cutting, die-cutting, and slitting can be done with ease.

### IMPORTANT NOTICE

Published information concerning Qualita products is based upon research and information which the Company believes to be reliable although such information does not constitute a warranty. The seller shall not be liable for damages in excess of the purchase price of the product nor for incidental or consequential damages.