

TECHNICAL DATA ▶

Physical Properties		Indoor Decorative	Outdoor Durable
Finish		Various - See Chart	Various - See Chart
Color		Various - See Chart	Various - See Chart
Adhesive		Clear permanent acrylic	Clear permanent acrylic
Film		Metallized PVC	UV-resistant metallized PVC
Liner		143 gsm one side PE-coated white kraft paper	143 gsm one side PE-coated white kraft paper
Opacity		2,2 minimum	2,2 minimum
Thickness	Film	65 microns	65 microns
	Film + Adhesive	90 microns	90 microns
Adhesion*	Stainless Steel	28 N/100 mm	Good adhesion to a wide variety of signs
Weight	Film + Adhesive	127 - 142 gsm	127 - 142 gsm
	Total w/ Liner	270 - 290 gsm	270 - 290 gsm

*Note: To ensure optimum service life, we recommend that all exterior applications are edge sealed (with a graphic edge sealer)

Conditions for Use		Indoor Decorative	Outdoor Durable
Shelf Life		1 year	1 year
Outdoor Durability		Indoor use only	Up to 3 years*
Min Application Temp		4° C	4° C
Service Temp Range		-29° to 55° C	-29° to 55° C
Solvent Resistance		Yes	Yes
Water Resistance		No	No**

**Edge sealing is recommended in high solvent exposure areas

The information provided herein is correct to the best of Nekoosa's knowledge. No liability for any errors, facts or opinions are accepted. Customers must satisfy themselves as to the suitability of this product for their application. No responsibility for any loss as a result of any person placing reliance on any material contained herein will be accepted.