

## Product

Product description	Permanent, self-adhesive, monomeric soft-PVC; gloss white
Product use	Screen and Offset print vinyl for UV screen printing and UV-Offset with suitable inks.

## Typical technical values

### Face

Face description	Monomeric soft-PVC; gloss white		
Substance	125	g/m <sup>2</sup>	DIN EN ISO 534
Caliper	95	µm	DIN EN ISO 2286-3
Stretch at break MD	> 160	%	DIN EN ISO 527
Tear resistance MD	>26	MPA	DIN EN ISO 527

### Adhesive

Type	Permanent		
Composition	Waterborne acrylic		
Adhesive description	Permanent, transparent, solvent-free polyacrylate adhesive with controlled initial tack and outstanding weeding properties.		
Peel	14	N/25mm	FTM 1 24h on Glass

### Liner

Liner description	Chlorine-free, bleached kraft liner		
Liner use	Kraft paper release liner for outstanding flatness.		
Substance	135	g/m <sup>2</sup>	DIN EN ISO 536
Caliper	127	µm	DIN EN ISO 534

### Performance

Rec. application temperature	Min. 10 °C
Service temperature	-30 °C to +90 °C
Durability	2-3 years
Shelf life	From date of delivery: 24 months under FINAT defined storage conditions (20-25 °C and RH 40-50%). Prolonged storage at higher temperatures and/or humidity levels will shorten the shelf life.
Dimension stability	Adhered to steel, no shrinkage in CD, in MD 0,4 mm max according to FINAT 14