

93800

Product Description

93800 is a double sided PVC tape with acrylic adhesive. It has strong initial adhesive power and is excellent for applying to plastic moldings and metals.

Performance Features

Strong initial adhesive strength.
Suitable on rough and embossed surfaces.

Applications

Applications to plastic moldings and metals.
Fixing and bonding panels.
In the automotive industry it can be applied to interior panels as well as exterior side mirrors.

Technical information

Adhesive	Solvent Acrylic
Carrier Thickness (mm)	0.08
Adhesive Thickness (mm)	0.16
Total Thickness (mm)	0.24
Colour	White
Adhesion to Steel (N/25mm)	30
Tensile Strength (N/25mm)	50
Temperatrue Range (°C)	Between -20 and +90
Liner	Havana Paper
Liner Type weight	80 gr
Ultra Violet resistance	No
Plasticiser Migration resistance	No
External usage	Fair

Important: The performance of all adhesive products is affected by many factors: heat, humidity, type of substrate, texture, inks used, and application technique. Our suggestions and recommendations concerning the use and application of our products are based on tests we believe are reliable. However, the purchaser must test the suitability of our products for his intended use under his own operating conditions. American BiltRite Inc. Assumes no liability for claims beyond the replacement value of any defective products, and is no way for consequential or incidental damages. These products are not suitable for prolonged outdoor exposure.

