

## PRODUCT INFORMATION

### PF 34/105 WP PV2 AT TRANSPARENT

Article number:	4005001	
Description of the Product:	Film backing:	Polyethylene
	Color:	clear
	Adhesive type:	Acrylic, water based
Technical data:	Thickness:	105 µm***
	Adhesion to stainless steel :	340 +68/-68 cN/25mm / 1.36 +0.27/-0.27 N/cm (AFERA 4001)*
Application:	The PF 34/105 WP PV2 AT TRANSPARENT is recommended for the protection of sensitive surfaces against dirt and damage during processing. When applied correctly, the film can be removed without leaving any residues. As per our actual knowledge, the film is suitable for e.g. the following surfaces:  - Application tape	
Application conditions:	- The surface must be free from oil, fat, dust and solvents - Room temperature (> 10°C and < 40°C)	
Resistance:	- Against moisture:	Moderate
	- Against oil:	Low
	- Against solvents:	Low
	- Against UV:	Low
Storage conditions of rolls:	- Room temperature (> 10°C and < 40°C) - Storage time max. 6 months after date of production - No direct exposure to sunlight and moisture	

\* Modified according to internal method for protective tapes

\*\*\* Internal method of measurement

**Note:**

The data and recommendations are given in good faith, on the basis of practical experience, but without warranty. The data stated above are average values of the production and are subject to tolerances of +/- 15%. The aforementioned characteristics are valid for standard surfaces. The film's performance may differ on specific surfaces, when applied under specific conditions. For this reason, it is highly recommended to the customer to carry out own tests under own specific conditions.

Technical modifications reserved.

All claims regarding liability and responsibility are based on the individual arrangements in the contract agreement, if not superseded by legal regulations.

Status: 01/12/2018 Rev. 01/12/2018